

Coil Nailer DC/55-572C

12100673



Fastener type

- BeA Nails BDC
- Diameter: 2,1 - 2,4 mm
- Length: 30 - 55 mm

Product strengths

- Adjustable ventilation
- Contact release
- Integrated noise reduction
- Optional suspension

Scope of operation

Carpentry, Industrial packaging, Pallet construction and repair, Roofing and facade, Wood packaging

Scope of delivery

Hex key, Service Instructions, Service oil, Sparepart list, User manual

More details:




Technical data

EAN	4045759061441
Type of fastener	BeA Nails BDC
Fastener diameter min	2,1 mm
Fastener diameter max	2,4 mm
Fastener length min	30 mm
Fastener length max	55 mm
Tool magazin slope	16 °
Magazine capacity max	1 coil
Weight	2,55 kg
Driving system	Compressed air
Activation method	Contact activation
Operating pressure min	5 bar
Operating pressure max	8 bar
Air consumption per drive operation	1,5 l (6 bar)
Tool length	293 mm
Tool width	130 mm
Tool height	270 mm
BG eligible for funding	No
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	92,6 dB(A)
Noise characteristic L WA. 1s, d according to EN 12549	98,2 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)

Technical data

Vibration value ahd according to ISO 8662	3,85 m/s ²
Vibration value Ka according to ISO 8662	2,5 m/s ²
Weight incl. packaging	3,49 kg

Related fastener



BeA Nails BDC
 · Diameter: 2,1 - 2,3 mm
 · Length: 30 - 55 mm

Item No.	Diameter x Length	Nail shank	Material
10500375	2,2 mm x 45 mm	Smooth shank	Steel, bright
10500376	2,2 mm x 50 mm	Smooth shank	Steel, bright
10500380	2,2 mm x 45 mm	Ring shank	Steel, bright
10500381	2,2 mm x 50 mm	Ring shank	Steel, bright
10500394	2,1 mm x 45 mm	Clinch	Steel, bright
10500397	2,3 mm x 55 mm	Smooth shank	Steel, bright
10500426	2,2 mm x 55 mm	Smooth shank	Steel, bright
10500442	2,1 mm x 55 mm	Clinch	Steel, bright
10500449	2,1 mm x 35 mm	Clinch	Steel, bright
10500477	2,2 mm x 55 mm	Ring shank	Steel, bright
10500479	2,1 mm x 40 mm	Clinch	Steel, bright
10500617	2,1 mm x 30 mm	Smooth shank	Steel, bright
10500619	2,1 mm x 30 mm	Ring shank	Steel, bright
10500622	2,1 mm x 30 mm	Ring shank	Steel, galvanized
10500625	2,1 mm x 32 mm	Ring shank	Steel, bright
10500627	2,1 mm x 32 mm	Ring shank	Steel, galvanized
10500628	2,1 mm x 35 mm	Smooth shank	Steel, bright
10500629	2,1 mm x 35 mm	Ring shank	Steel, bright
10500634	2,1 mm x 38 mm	Ring shank	Steel, bright
10500637	2,1 mm x 40 mm	Smooth shank	Steel, bright
10500639	2,1 mm x 40 mm	Ring shank	Steel, bright
10500642	2,1 mm x 40 mm	Ring shank	Steel, galvanized
10500644	2,1 mm x 45 mm	Smooth shank	Steel, bright
10500646	2,1 mm x 45 mm	Ring shank	Steel, bright
10500650	2,1 mm x 50 mm	Smooth shank	Steel, bright
10500651	2,1 mm x 50 mm	Clinch	Steel, bright
10500652	2,1 mm x 50 mm	Ring shank	Steel, bright

10500653	2,1 mm x 50 mm	Ring shank	Steel, galvanized
10500654	2,1 mm x 55 mm	Smooth shank	Steel, bright
10500656	2,1 mm x 55 mm	Ring shank	Steel, bright
10500795	2,1 mm x 35 mm	Clinch	Steel, bright
10500803	2,1 mm x 40 mm	Clinch	Steel, bright
10500936	2,1 mm x 35 mm	Ring shank	Steel, bright
10501220	2,2 mm x 55 mm	Screw shank	Steel, bright
10501487	2,1 mm x 45 mm	Ring shank	Steel, bright
10501717	2,3 mm x 40 mm	Ring shank	Steel, bright
10501718	2,3 mm x 45 mm	Ring shank	Steel, bright
10501719	2,3 mm x 50 mm	Ring shank	Steel, bright
10501720	2,3 mm x 55 mm	Ring shank	Steel, bright
10501722	2,3 mm x 55 mm	Screw shank	Steel, bright
10501870	2,1 mm x 32 mm	Ring shank	Steel, bright
10502269	2,15 mm x 55 mm	Smooth shank	Steel, bright
10502278	2,2 mm x 50 mm	Ring shank	Steel, bright

Other variations and sizes on request